



Optional
Remotely controlled
via web access



Optional
Remotely controlled
via web access



MemPro 12000DD-20000DD SS

- Superior quality & performance
- Unimodular design
- Positive recirculation on membrane elements
- Stainless steel double ladder frame & plumbing
- Stainless steel pumps with Industrial motors (top mounted)
- Stainless steel integrated CIP tank
- Ventilated stainless steel electrical box
- Permeate & concentrate valve panel
- Option of expansion up to 20 elements & 5 high pressure pumps
- Programmable logic controller
- Conductivity meter & digital temperature monitor
- Low pressure & high temperature safety
- 2 independant banks of 7 X 20 inch filters in SS
- Strainer included
- 5 years limited warranty

Options :

- + Wash water management with pH meter
- + Drainage by air «Mempro Flush» patent # US 8,889,001 B2
- + Individual vessel permeate flowmeters
- + HMI with web access
- + Interstages booster pump
- + Inline brix monitor
- + SS plumbing
- + SS soap filter
- + Complete automation
- + 230V - 460V - 600V - 3 phases

MemPro 4000D-10000D SS

- Superior quality & performance
- Unimodular design
- Positive recirculation on membrane elements
- Stainless steel construction frame & plumbing
- Stainless steel pumps with Industrial motors (top mounted)
- Stainless steel integrated CIP tank
- Ventilated stainless steel electrical box
- Permeate & concentrate valve panel
- Option of expansion up to 20 elements & 5 high pressure pumps
- Programmable logic controller
- Conductivity meter & digital temperature monitor
- Low pressure & high temperature safety
- 2 independant banks of 3 X 20 inch filters
- Strainer included
- 5 years limited warranty

Options :

- + Drainage by air «Mempro Flush» patent # US 8,889,001 B2
- + Individual vessel permeate flowmeters
- + HMI with web access
- + Interstages booster pump
- + Inline brix monitor
- + SS plumbing
- + Soap filter
- + Complete automation
- + 230V - 460V - 600V - 3 phases
- + 1 independant bank of 7 X 20 inch filters in SS

Model	Membrane Quantity	Prefilter 5 microns	Feed Pump	Pressure Pump	Recirculation Pump	Amps. 240 volts	Dimensions (L x D x H)
MemPro 12000DD-SS	12 x 8"	2 x 7 x 20"	5 hp	2 x 7,5 hp	6 x 3 hp	160,2	112" x 50" x 75"
MemPro 14000DD-SS	14 x 8"	2 x 7 x 20"	5 hp	3 x 7,5 hp	7 x 3 hp	204	112" x 50" x 75"
MemPro 16000DD-SS	16 x 8"	2 x 7 x 20"	5 hp	3 x 7,5 hp	8 x 3 hp	217	112" x 50" x 75"
MemPro 18000DD-SS	18 x 8"	2 x 7 x 20"	7,5 hp	4 x 7,5 hp	9 x 3 hp	297	112" x 50" x 75"
MemPro 20000DD-SS *	20 x 8"	2 x 7 x 20"	7,5 hp	4 x 7,5 hp	10 x 3 hp	310	112" x 50" x 96"

Model	Membrane Quantity	Prefilter 5 microns	Feed Pump	Pressure Pump	Recirculation Pump	Amps. 240 volts	Dimensions (L x D x H)
MemPro 4000D-SS	4 x 8"	6 x 20"	1 x 3 hp	2 x 5 hp	2 x 3 hp	82	109" x 34" x 76"
MemPro 6000D-SS	6 x 8"	6 x 20"	1 x 3 hp	3 x 5 hp	3 x 3 hp	114	109" x 34" x 76"
MemPro 8000D-SS *	8 x 8"	6 x 20"	1 x 3 hp	2 x 7,5 hp	4 x 3 hp	137	109" x 36" x 76"
MemPro 10000D-SS	10 x 8"	6 x 20"	1 x 5 hp	2 x 7,5 hp	5 x 3 hp	157	109" x 36" x 96"

* picture above