



Optional

Remotely controlled via web access

MemPro 1200 V - 2400 V-SS

- Superior quality & performance
- Compact
- Easy & simplified operation
- Positive recirculation on membrane elements
- Stainless steel frame & plumbing
- Mounted on casters
- Stainless steel recirculation pump with industrial motor (top mounted)
- Stainless steel electrical box
- Stainless steel modular CIP tank
- Permeate & concentrate valve panel
- Option of expansion up to 4 elements, 2 high pressure pumps
- Programmable controller
- Low pressure & high temperature safety protection
- Feed pump & 2 filter housings (20")
- Digital conductivity monitor
- 5 years limited warranty

Options :

- + Inlet strainer 1.5"
- + Horizontal element support
- + Remotely controlled via web access
- + Inline brix monitor
- + 230V - 460V - 600V - 3 phases

Model	Membrane Quantity	Prefilter 5 microns	Feed Pump	Pressure Pump	Recirculation Pump	Amps. 240 volts	Dimensions (L x D x H)
MemPro 1200 V-SS *	2 x 8"	2 x 20"	2,5 hp	1 x 5 hp	2 x 1,5 hp	45	80" x 24" x 64"
MemPro 1800 V-SS	3 x 8"	2 x 20"	2,5 hp	1 x 7,5 hp	3 x 1,5 hp	64	100" x 24" x 64"
MemPro 2400 V-SS	4 x 8"	2 x 20"	2,5 hp	1 x 7,5 hp	4 x 1,5 hp	71	120" x 24" x 64"

* picture above