



**Optional**

Remotely controlled via web access

## MemPro 100-200 H-SS

- Superior quality & performance
- Affordable & compact
- Frost protection - drainable conception
- Horizontal installation on top of sap tank
- No need of concentrate tank (batch concentration)
- 10 minutes fast & simple installation
- Low electrical power consumption
- Easy & simplified operation
- Positive recirculation on membrane elements
- Stainless steel frame & plumbing
- Mounted on casters
- Stainless Steel recirculation pump
- SS high efficiency pressure pumps
- Low pressure and high temperature safety protection
- 10 inch filter housing
- Strainer included
- 5 years limited warranty
- Patent # CA 2,642,050 & # US 8,025,799

**Options :**

- + GFCI Breaker (must be used when installation above sap tank)
- + Concentrate & permeate valve panel
- + Inlet strainer 1 po

Model Ga/hour	Membrane Quantity	Prefilter 5 microns	Pressure Pump	Recirculation Pump	Amps. 120 volts	Weight (lbs)	Dimensions (L x D x H)
MemPro100 H-SS	1 x 4"	1 x 10"	½ hp	½ hp	14	150	50" x 16" x 21"
Mempro 200 H-SS *	2 x 4"	1 x 10"	¾ hp	½ hp	18	175	50" x 16" x 21"

\* picture above