



Optional

Remotely controlled via web access

MemPro 4000 D - 10000 D-SS

- Superior quality & performance
- Unimodular design
- Positive recirculation on membrane elements
- Stainless steel construction frame & plumbing
- Stainless steel pumps with Industrial motors (top mounted)
- Stainless steel integrated CIP tank
- Ventilated stainless steel electrical box
- Permeate & concentrate valve panel
- Option of expansion up to 20 elements & 5 high pressure pumps
- Programmable logic controller
- Conductivity meter & digital temperature monitor
- Low pressure & high temperature safety
- 2 independant banks of 3 X 20 inch filters
- Strainer included
- 5 years limited warranty

Options :

- + Drainage by air «Mempro Flush» patent # US 8,889,001 B2
- + Individual vessel permeate flowmeters
- + HMI with web access
- + Interstages booster pump
- + Inline brix monitor
- + SS plumbing
- + Soap filter
- + Complete automation
- + 230V - 460V - 600V - 3 phases
- + 1 independant bank of 7 X 20 inch filters in SS

Model	Membrane Quantity	Prefilter 5 microns	Feed Pump	Pressure Pump	Recirculation Pump	Amps. 240 volts	Dimensions (L x D x H)
MemPro 4000 D-SS	4 x 8"	6 x 20"	1 x 3 hp	2 x 5 hp	2 x 3 hp	82	109" x 36" x 76"
MemPro 6000 D-SS	6 x 8"	6 x 20"	1 x 3 hp	3 x 5 hp	3 x 3 hp	114	109" x 36" x 76"
MemPro 8000 D-SS *	8 x 8"	6 x 20"	1 x 5 hp	2 x 7.5 hp	4 x 3 hp	139	109" x 36" x 76"
MemPro 10000 D-SS	10 x 8"	6 x 20"	1 x 5 hp	2 x 7.5 hp	5 x 3 hp	157	109" x 36" x 96"

* picture above