

MemPro 1200 V - 2400 V-SS

REVERSE OSMOSIS
SÉRIE MEMPRO-SS EN ACIER INOX

- Superior quality & performance
- Compact
- Easy & simplified operation
- Positive recirculation on membrane elements
- Stainless steel frame & plumbing
- Mounted on casters
- Stainless steel recirculation pump with industrial motor (top mounted)
- Stainless steel electrical box
- Stainless steel modular CIP tank
- Permeate & concentrate valve panel
- Option of expansion up to 2 elements, 2 high pressure pumps
- Low pressure & high temperature safety protection
- Feed pump & 2 filter housings (20")
- Digital conductivity monitor
- 5 years limited warranty



Options

- + Inlet strainer 1.5"
- + Horizontal element support
- + Remotely controlled via web access
- + Inline brix monitor
- + 230V - 460V - 600V - 3 phases



Optional
Remotely controlled
via web access

Model	Membrane Quantity	Prefilter 5 microns	Feed pump	Pressure pump	Recirculation pump	Amps. 240 volts	Dimensions (WxDxH)
MemPro 1200 V-SS*	2 x 8"	2 x 8"	2 hp	1 x 5 hp	2 x 1,5 hp	46	80" x 24" x 64"
MemPro 1800 V-SS	3 x 8"	3 x 8"	2 hp	1 x 7,5 hp	3 x 1,5 hp	66	100" x 24" x 64"
MemPro 2400 V-S	4 x 8"	4 x 8"	2 hp	1 x 7,5 hp	4 x 1,5 hp	73	120" x 24" x 64"

*Model identified in the picture